

# Saxomer<sup>®</sup> X Flex

Saxomer X Flex is a thermoplastic elastomer, optimally adapted for extrusion. Due to its specially developed material structure, it is particularly suitable for profiles, hoses or sealing components.

## Advantages of the Saxomer X Flex

- High customer satisfaction
- Optimised for Extrusion and Coextrusion
- Easy conversion from PVC
- Lucrative EPDM substitution
- From low-budget to high-premium

## Range for extrusion TPE

- Hardness 35A - 90A
- Density 0.89 - 1.18

## Key properties

- RAL-GZ 695, CSTB, UL or KTW certified
- Processing from 130 °C
- Adapted haptics: from smooth to soft-touch
- Very good colouring
- UV and ozone resistant
- Electrically conductive
- Foamable for lower density



Contact us - we will be  
happy to advise you.  
+49 (0) 3423 661 0  
info@pcw.gmbh

[www.pcw.gmbh](http://www.pcw.gmbh)



### Innovative and Competent

With a passion for technical perfection and a sure feeling for market requirements and developments, PCW GmbH is the specialist for compounds under the umbrella of Advance Holding.

Today, Advance Holding generates a revenue of more than 520 million euros with approximately 800 employees and has significant market experience and large production capacities at all together five locations in Germany and North America.

For more information, please visit our website or feel free to contact us personally.



+49 3423 661 0



info@pcw.gmbh



www.pcw.gmbh

**Innovative and Competent – Your right partner for compounding.** At its facility in the richly traditional town of Eilenburg, Germany, PCW GmbH focuses on the development and production of tailor-made compounds.

#### PCW GmbH

Am Alten Celluloidwerk 7  
D-04838 Eilenburg

phone: +49 3423 661 0

fax: +49 3423 661 485

**www.pcw.gmbh**



The content of this publication is provided for information only. PCW GmbH does not assume any liability concerning accuracy, reliability or completeness of the information contained in this publication. There is no guarantee for its completeness and it shall not be used for technical specification purposes. At its own discretion PCW GmbH may revise the information in the present publication at any time without announcement.