

# Saxene<sup>®</sup> Polypropylen Compounds

eco

Into the Future of the Automotive Industry with Sustainable Plastics

series	testing/trial	development					
SAXENE ECO Type	Filler content [%]	MFI (230/2.16) [g/10min]	Tensile e-module [MPa]	Charpy notched impact [kJ/m <sup>2</sup> ]	Recyclate content	Examples of application	Features
Saxene PP 6320 GF30 BK	30	12	7000	8	35% - PIR	Frontend-KUM	high heat stability,
Saxene PP 6350 GF20 BK	20	12	4200	16	40% - PCR	Frontend-KUM, locking part	UV-stability, Impact resistant, impact modified
Saxene PP 6352 TC20 BK113	20	25	2100	2,5	40% - PIR	Exterior visible	heat stability, color-stable
Saxene PP 6351 GF30 BK	30	12	7000	8	35% - PIR	Lower stiffener	UV-stability
Saxene PP 6370 GF20 BK	20	11	4800	11	28% - PCR	Instrument panel carrier	heat stability, low emission**
Saxene PP 6370 TC20 BK	20	19	2100	5	28% - PCR	Instrument panel carrier	heat stability, low emission**
Saxene PP 6311 GF30 BK	30	10	6200	10	35% - PCR	Interior	low-emission**, UV-stability
Saxene PP 6350 GF30 BK	30	9	5000	18	35% - PCR	Interior	
Saxene PP 6453 TC20 BK	20	18	2300	2,5	50% - PCR	Exterior visible	heat stability
Saxene PP 6350 TC20 BK111	20	12	1300	40 (P)*	28% - PCR	Exterior visible	UV-stability
Saxene PP 6590 TC12 BK102	12	30	1000	35 (P)*	35% - PCR	Exterior visible	UV-stability, color-stable
Saxene PP 6590 TC28 BK102	28	20	1500	25 (P)*	40% - PCR	Exterior visible	UV-stability, color-stable
Saxene PP 6322 GF30 BK	30	12	7000	8	35% - PCR	Frontend-KUM, locking part	high heat stability
Saxene PP 6322 GF40 BK	40	10	9000	8	30% - PCR	Frontend-KUM, locking part	high heat stability
Saxene PP 6323 GF40 BK	40	10	9000	8	30% - PCR	Exterior visible	heat stability
Saxene PP 6323 GF30 BK	30	12	7000	8	35% - PCR	Exterior visible	heat stability
Saxene PP 6353 GF30 BK	30	12	7000	8	35% - PCR	Exterior	high heat stability, UV-stability
Saxene PP 6311 GF40 BK	40	8	8400	10	30% - PCR	Interior	low-emission**, UV-stability,
Saxene PP 6312 GF30 BK116	30	12	6500	10	30% - PCR	Interior visible	low-emission**, UV-stability
Saxene PP 6250 GF40 BK	40	8	7400	9	30% - PCR	Interior	low-emission**, UV-stability
Saxene PP 6355 TC16 BK116	16	14	1400	25	40% - PCR	Interior visible	color-stable, impact-modified
Saxene PP 6353 GF20 BK	20	12	4800	5,5	40% - PCR	Exterior visible	high heat stability, UV-stability
Saxene PP 6353 GF40 BK	40	10	9000	8	30% - PCR	Exterior visible	high heat stability, UV-stability
Saxene PP 6590 TC15 BK102	15	28	1100	33	35% - PCR	Exterior visible	UV-stability
Saxene PP 6590 TC20 BK	20	20	1400	16	40% - PCR	Exterior visible	UV-stability

\*(P) = partiell

\*\* Testergebnisse für Emissionen und Geruch extern evaluiert und auf Anfrage verfügbar.

# Saxene<sup>®</sup> Polypropylen Compounds **eco**

*Into the Future of the Automotive Industry with Sustainable Plastics*

## Exterior visible / Water guard strips

Saxene PP 6323 GF30 BK 35% PCR

Saxene PP 6323 GF40 BK 30% PCR

## Exterior visible / Water tank cover

Saxene PP 6352 TC20 BK113 40% PIR

Saxene PP 6453 TC20 BK 50% PCR

## Exterior / Frontend-KUM

Saxene PP 6320 GF30 BK 35% PIR

Saxene PP 6350 GF20 BK 40% PCR

Saxene PP 6322 GF30 BK 35% PCR

Saxene PP 6322 GF40 BK 30% PCR

## Exterior / Lower stiffener

Saxene PP 6351 GF30 BK 35% PIR

Saxene PP 6353 GF20 BK 40% PCR

Saxene PP 6353 GF30 BK 35% PCR

Saxene PP 6353 GF40 BK 30% PCR

## Exterior / Front- & rear bumper, spoiler

Saxene PP 6590 TC12 BK102 35% PCR

Saxene PP 6590 TC15 BK102 35% PCR

Saxene PP 6590 TC20 BK 40% PCR

Saxene PP 6590 TC28 BK102 41% PCR

Saxene PP 6350 TC20 BK111 25% PCR

## Interior / Roof frame

Saxene PP 6311 GF40 BK 30% PCR

## Interior visible / Trim covers

Saxene PP 6355 TC16 BK116 >40% PCR

## Interior / Door module carrier

Saxene PP 6311 GF30 BK 35% PCR

## Interior / Instrument panel carrier

Saxene PP 6370 GF20 BK 28% PCR

Saxene PP 6370 TC20 BK 28% PCR

## Interior visible / Storage support

Saxene PP 6312 GF30 BK116 30% PCR

## Interior / Carrier

Saxene PP 6350 GF30 BK 35% PCR

## Interior / Carrier

Saxene PP 6250 GF40 BK 30% PCR



The content of this publication is provided for information only. PCW GmbH does not assume any liability concerning accuracy, reliability or completeness of the information contained in this publication. There is no guarantee for its completeness and it shall not be used for technical specification purposes. At its own discretion PCW GmbH may revise the information in the present publication at any time without announcement.